



# FULL SYNTHETIC

WWW.REXLUBE.COM



## THE LATEST IN HIGH-TECHNOLOGY LUBRICATION

– ALL PRODUCTS ARE CERTIFIED AND BONDED BY THE MANUFACTURER'S 5 MILLION DOLLAR LIABILITY INSURANCE. –



# ATF-MV



### Maximum Protection

- Full synthetic maximum wear protection
- Suitable for a broad range of vehicles

### Low Viscosity

- Excellent low temperature performance
- Lower friction for smoother shifting

### Extended Life

- Long fluid life and extended wear protection
- Superior shear stability performance

ATF-MV is a full synthetic fluid providing maximum protection for a wide range of modern and high-performance transmissions.

V231127

## MEETS OR EXCEEDS OEM PERFORMANCE STANDARDS

| GRADE                     | Test Method | ATF-MV      |
|---------------------------|-------------|-------------|
| Color                     | Visual      | Red         |
| Viscosity @ 100°C, cSt    | ASTM D445   | 5.8         |
| Viscosity @ 40°C, cSt     | ASTM D445   | 32.9        |
| Viscosity Index           | ASTM D2270  | 180         |
| Pour Point, °C/°F         | ASTM D97    | -51 / -59.8 |
| Flash Point, COC °C/°F    | ASTM D92    | 204 / 399.2 |
| API Gravity               | ASTM D287   | 32.6        |
| Brookfield Vis.cP @ -40°C | ASTM D2983  | 16200       |

- ▶ ALLISON TES-389, V-730D, C-4
- ▶ AISIN WARNER JWS 3324 (WS)
- ▶ AISIN WARNER AW-1
- ▶ BMW 7045E, 8072B
- ▶ BMW LA 2634, LT 71141
- ▶ BMW 83 22 0 142 516
- ▶ CATERPILLAR TO - 2
- ▶ CHRYSLER ATF +4, +3
- ▶ DEXRON®-VI,
- ▶ DEXRON, -IIH, -IIIG, -IIE, -II
- ▶ FORD MERCON® V, FNR5
- ▶ GM TASA
- ▶ GMW16444
- ▶ HONDA ATF Z1, DW-1
- ▶ HYUNDAI/KIA SP-II, -III, -IV
- ▶ HYUNDAI/KIA JWS 3314, 3317
- ▶ HYUNDAI NWS-9638
- ▶ IDEMITSU K17 (JATCO)
- ▶ JASO 1A, 1A-LV, M315-1A
- ▶ KIA RED-1
- ▶ MAZDA ATF F-1, M-III, M-V
- ▶ MB 236.41, 236.10, NAG 1
- ▶ MB 236.12 .14 .15 / 236.1 .2 .3
- ▶ MB 236.5 .6 .7 .9 .11 .81
- ▶ MITSUBISHI DIAQUEEN J2, J3
- ▶ MITSUBISHI SP-II, SP-III, SP-IV
- ▶ NISSAN MATIC D, J, K, S, W
- ▶ PSA AL-4
- ▶ RENAULT DP-0
- ▶ SAAB 3309, 93 165 147
- ▶ SATURN T-IV FLUID
- ▶ SUBARU ATF, ATF-HP
- ▶ SUZUKI 3314, 3317
- ▶ TOYOTA T, T-II, T-III, T-IV
- ▶ TOYOTA WS (JWS 3324)
- ▶ VOITH TRANSMISSION
- ▶ VOLVO 97342
- ▶ VOLVO 4, 6 SPEED, 1161540
- ▶ VW G 052 162, -990, -540
- ▶ VW G 055 005, -025, -162
- ▶ ZF TE-ML 09, 11 (3/4/5 SPEED)
- ▶ ZF 6 SPEED (S671 090 255)

**Typical Characteristics** Typical test data are average values only. Minor variations, which do not affect performance, may occur.

**HANDLING AND SAFETY INFORMATION** - Refer to REX (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.